MTN668990

Lead gel battery, 7.2 Ah





Main

Range of product	KNX	
Product or component type	Battery	
Battery type	Lead gel	

Complementary

[Ue] rated operational voltage	12 V
Battery capacity	7.2 Ah
Material	Plastic: box
Height	100 mm
Width	65 mm
Length	151 mm

Environment

Ambient air temperature for operation	-1540 °C	

Packing Units

Number of Units in Package 1 1 Package 1 Height 8.300 cm Package 1 Width 12.700 cm Package 1 Length 16.100 cm Package 1 Weight 2.564 kg Unit Type of Package 2 BB1 Number of Units in Package 2 2 Package 2 Height 9.900 cm Package 2 Width 17.800 cm Package 3 Length 26.300 cm	Unit Type of Package 1	PCE	
Package 1 Width 12.700 cm Package 1 Length 16.100 cm Package 1 Weight 2.564 kg Unit Type of Package 2 BB1 Number of Units in Package 2 2 Package 2 Height 9.900 cm Package 2 Width 17.800 cm	Number of Units in Package 1	1	
Package 1 Length 16.100 cm Package 1 Weight 2.564 kg Unit Type of Package 2 BB1 Number of Units in Package 2 2 Package 2 Height 9.900 cm Package 2 Width 17.800 cm	Package 1 Height	8.300 cm	
Package 1 Weight 2.564 kg Unit Type of Package 2 BB1 Number of Units in Package 2 2 Package 2 Height 9.900 cm Package 2 Width 17.800 cm	Package 1 Width	12.700 cm	
Unit Type of Package 2 Number of Units in Package 2 Package 2 Height Package 2 Width 17.800 cm	Package 1 Length	16.100 cm	
Number of Units in Package 2 2 Package 2 Height 9.900 cm Package 2 Width 17.800 cm	Package 1 Weight	2.564 kg	
Package 2 Height 9.900 cm Package 2 Width 17.800 cm	Unit Type of Package 2	BB1	
Package 2 Width 17.800 cm	Number of Units in Package 2	2	
	Package 2 Height	9.900 cm	
Dackage 2 Length 26 200 cm	Package 2 Width	17.800 cm	
Fackage 2 Length 20.500 Cm	Package 2 Length	26.300 cm	
Package 2 Weight 5.310 kg	Package 2 Weight	5.310 kg	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	€Yes

Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End Of Life Information	
Contractual warranty		

18 months

Warranty