



Main

| | |
|---------------------------|---------------------|
| Range of product | KNX |
| Product or component type | KNX DALI gateway |
| Bus type | KNX |
| Function available | Updateable software |

Complementary

| | |
|--------------------------------|-------------|
| Total number of 18 mm modules | 4 |
| Mounting support | DIN rail |
| [Ue] rated operational voltage | 100...240 V |
| Network frequency | 50/60 Hz |
| Communication port protocol | DALI |
| Local signalling | LED |

Environment

| | |
|-------------------------|------|
| IP degree of protection | IP20 |
|-------------------------|------|

Packing Units

| | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 8.200 cm |
| Package 1 Width | 13.300 cm |
| Package 1 Length | 15.800 cm |
| Package 1 Weight | 208.000 g |
| Unit Type of Package 2 | S04 |
| Number of Units in Package 2 | 28 |
| Package 2 Height | 30.000 cm |
| Package 2 Width | 40.000 cm |
| Package 2 Length | 60.000 cm |
| Package 2 Weight | 6.384 kg |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |

| | |
|--------------------------|---|
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
