



Main

Range of product	SpaceLogic KNX
Product or component type	KNX DALI gateway
Bus type	KNX
Function available	Updateable software

Complementary

Total number of 18 mm modules	4
Mounting support	DIN rail
[Ue] rated operational voltage	100...240 V
Network frequency	50...60 Hz
Communication port protocol	DALI
Web services	HTTP server
Local signalling	LED

Environment

IP degree of protection	IP20
-------------------------	------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8 cm
Package 1 Width	12.5 cm
Package 1 Length	15.7 cm
Package 1 Weight	275 g
Unit Type of Package 2	S04
Number of Units in Package 2	28
Package 2 Height	30 cm
Package 2 Width	40 cm
Package 2 Length	60 cm
Package 2 Weight	8.603 kg
Unit Type of Package 3	P12
Number of Units in Package 3	112
Package 3 Height	45 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	47 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins