



## Main

Range	ClimaSys
Product name	ClimaSys CC
Product or component type	Electronic hygrotherm
Temperature setting range	-40...80 °C
Humidity setting range	20...80 %
Display type	OLED screen
Information displayed	Relative humidity Temperature in °C Temperature in °F

## Complementary

Input voltage	9...30 V AC/DC
Sensor type	Optional NTC external sensor
Maximum switching capacity	4 A 30 V AC/DC
Electrical connection	8 connectors, clamping capacity: 2.5 mm <sup>2</sup>
Mounting mode	Clipped By screws
Height	External: 85 mm
Width	External: 56 mm
Depth	External : 44 mm
Mounting location	On mounting plate 35 mm DIN rail Cross rails Spacial upright
Ambient air temperature for operation	-40...80 °C
Hysteresis	2 K programmed value
Hysteresis	3 %
Number of outputs	2 ventilation/heating function
Material	PC
Colour	Light grey
Flame retardance	Self-extinguishing conforming to UL94 (material V0)
Product certifications	UR

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.5 cm
Package 1 Width	7.5 cm
Package 1 Length	8.5 cm
Package 1 Weight	140.0 g
Unit Type of Package 2	PAL
Number of Units in Package 2	75
Package 2 Height	40.0 cm
Package 2 Width	40.0 cm

Package 2 Length	60.0 cm
Package 2 Weight	11.0 kg

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

### Contractual warranty

Warranty	18 months
----------	-----------