NSYCR20WU1C

ClimaSys PTC heating resistance 20W, 12-24V insulate

Green Premium™

Main

Range	ClimaSys
Product name	ClimaSys CR
Product or component type	Resistance heater
Power range	20 W
Input voltage	12...24 V DC
Electrical connection	4 screw terminals 2.5 mm²

Complementary

Operating position	Vertical
Ambient air temperature for operation	-40…70 °C
IP degree of protection	IP20
Electrical insulation class	Class II
Product certifications	VDE
Material	Body: extruded aluminium Cover: plastic
Height	External: 98 mm
Width	External: 38 mm
Depth	External : 75 mm
Condition of use	Heaters must be installed with a thermal controller Electrical protection is needed Air sealed enclosure
Fixing mode	By clips
Mounting support	35 mm DIN rail

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.5 cm
Package 1 Width	8 cm
Package 1 Length	11 cm
Package 1 Weight	204 g
Unit Type of Package 2	PAL
Number of Units in Package 2	10
Package 2 Height	20 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	2.04 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months

Life Is On | Schneider Electric