Product data sheet Characteristics

NSYCR55WU3

ClimaSys PTC heating resistance 55W, 270-420V





Main

Range	ClimaSys
Product name	ClimaSys CR
Product or component type	Resistance heater
Power range	55 W
Input voltage	270420 V AC 50/60 Hz

Complementary

Operating position	Vertical	
Ambient air temperature for operation	-4070 °C	
IP degree of protection	IP20	
Product certifications	VDE[RETURN]UL	
Material	Body: extruded aluminium	
Height	210 mm	
Width	90 mm	
Depth	70 mm	
Condition of use	Electrical protection is needed Air sealed enclosure Heaters must be installed with a thermal controller	
Fixing mode	By clips	
Mounting support	35 mm DIN rail	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.0 cm
Package 1 Width	8.0 cm
Package 1 Length	20.0 cm
Package 1 Weight	448.0 g
Unit Type of Package 2	P12
Number of Units in Package 2	200
Package 2 Height	80.0 cm
Package 2 Width	80.0 cm
Package 2 Length	120.0 cm
Package 2 Weight	120.0 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherenced as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the documentation is not be used to perform the appropriate and complete risk analysis, evaluation of the products with respect to the relevant specific application or use thereof. Neither Schmeider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	[™] China RoHS Declaration
RoHS exemption information	₽¥Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

warranty 18 months	Warranty	18 months
--------------------	----------	-----------