NSYCRP1W230VTVC

ClimaSys PTC heating resistance 350-500W, 230V insulate thermoventilator





Main

Range	ClimaSys
Product name	ClimaSys CR
Product or component type	Resistance heater with fan and thermostat
Power range	350 W 500 W
Input voltage	230 V AC 50/60 Hz
Electrical connection	2 screw terminals 2.5 mm ²

Complementary

o o in promontary		
Operating position	Vertical	
Ambient air temperature for operation	-4070 °C	
Temperature setting range	060 °C	
IP degree of protection	IP20	
Product certifications	UL[RETURN]VDE	
Height	150 mm	
Width	155 mm	
Depth	215 mm	
Condition of use	Air sealed enclosure Electrical protection is needed	
Fixing mode	By clips	
Mounting support	35 mm DIN rail	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	15.0 cm	
Package 1 Width	15.5 cm	
Package 1 Length	22.0 cm	
Package 1 Weight	1.02 kg	

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑REACh Declaration	
EU RoHS Directive	Compliant with Exemptions	
Mercury free	Yes	
China RoHS Regulation	☐ China RoHS Declaration	
RoHS exemption information	₽¥Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Warranty 18 months