NSYCUX600DG

Side Connected Cooling Unit, Climasys CU, Stainless Steel, 600W, 230V, 50/60Hz, IP55



Main	
Range	ClimaSys
Product name	CU
Product or component type	Cooling unit
Mounting type	Side
Installation	Indoor side
Product destination	For enclosure
Mounting mode	By screws
Supply Voltage	230 V AC at 50/60 Hz, 1 phase
Rated Power	650 W
Cooling power	650 W 50/60 Hz L35-L35 500 W 50/60 Hz L35-L50

Complementary

Height	460 mm	
Width	290 mm	
Depth	190 mm	
[In] rated current	2.3 A	
Inrush current	6 A	
Power consumption in W	350 W at 50/60 Hz, L35-L35 410 W at 50/60 Hz, L35-L50	
Energy efficiency ratio	1.8	
Control type	Electronic controller	
Temperature setting range	2050 °C at 50/60 Hz	
Ambient air temperature for operation	2050 °C at 50/60 Hz inside the enclosure: 555 °C at 50/60 Hz outside the enclosure:	
Noise level	55 dB	
Pressure	28 bar	
Flow rate	Internal circuit: 117 m3/h at 50/60 Hz External circuit: 174 m3/h at 50/60 Hz	
Net weight	11.7 kg	
Cooling gas type	R134a (0.110 kg)	
Type of filter	Optional external circuit filter	
Protection type	Circuit breaker protection: miniature circuit breaker (MCB)	
Protection type	Thermal protection: T 15 A Short-circuit protection (magnetic):	
Material	Stainless steel	
Colour	Stainless steel	

Environment

Product certifications	UL[RETURN]IEC	
Directives	2006/42/EC - machinery 2014/30/EU - electromagnetic compatibility	
	2011/65/EU - RoHS	
Standards	EN/ISO 12100	
	EN 60335-1	
	EN 60335-2-40	
	EN 61000-3-2	
	EN 61000-3-3	
	EN 61000-6-2	
	EN 61000-6-3	
	EN/IEC 63000:2018	
	EN 14511	
IP degree of protection	IP55 conforming to IEC 60529 (on the internal circuit)	
	IP24 conforming to IEC 60529 (on the external circuit)	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	52 cm
Package 1 Width	38 cm
Package 1 Length	22.5 cm
Package 1 Weight	13 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	4
Package 2 Height	66.4 cm
Package 2 Width	120 cm
Package 2 Length	80 cm
Package 2 Weight	77 kg

Offer Sustainability

REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	€Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins