# Product data sheet Characteristics

# NSYCUX800

# ClimaSys standard cooling unit side of enclosure - 820W at 230 V





#### Main

Range	ClimaSys
Product name	CU
Product or component type	Cooling unit
Mounting type	Side
Installation	Indoor side
Product destination	For enclosure
Mounting mode	By screws
Supply Voltage	230 V AC at 50/60 Hz, 1 phase
Rated Power	820 W
Cooling power	820 W 50/60 Hz L35-L35 680 W 50/60 Hz L35-L50

#### Complementary

Complementary	
Height	783 mm
Width	348 mm
Depth	215 mm
[In] rated current	2.6 A
Inrush current	10.8 A
Power consumption in W	440 W at 50/60 Hz, L35-L35 490 W at 50/60 Hz, L35-L50
Energy efficiency ratio	1.9
Control type	Electronic controller
Temperature setting range	2055 °C at 50 Hz 2050 °C at 60 Hz
Ambient air temperature for operation	2046 °C inside the enclosure: 55 °C maximum: 2055 °C at 50 Hz outside the enclosure: 2050 °C at 60 Hz outside the enclosure:
Noise level	65 dB conforming to EN/ISO 3746
Pressure	25 bar
Flow rate	Internal circuit: 330 m3/h at 50/60 Hz External circuit: 570 m3/h at 50/60 Hz
Net weight	27 kg
Cooling gas type	R134a (0.23 kg)
Type of filter	Optional external circuit filter
Protection type	Thermal protection: T 6 A Short-circuit protection (magnetic):
Material	Stainless steel
Colour	Grey (RAL 7035)

#### Environment

Product certifications	CE
Directives	2004/108/EC - electromagnetic compatibility 2006/42/EC - machinery 2006/95/EC - low voltage directive
Standards	EN/ISO 12100 EN 60335-1 EN 60335-2-40 EN 378 EN 60204-1
IP degree of protection	IP55 conforming to IEC 60529 (on the internal circuit) IP34 conforming to IEC 60529 (on the external circuit)

## Packing Units

•	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	21.5 cm
Package 1 Width	34.8 cm
Package 1 Length	78.3 cm
Package 1 Weight	27.0 kg
Unit Type of Package 2	P12
Number of Units in Package 2	6
Package 2 Height	100.0 cm
Package 2 Width	80.0 cm
Package 2 Length	120.0 cm
Package 2 Weight	176.2 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	€Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins