

Product data sheet

Characteristics

NSYCVF575M230MB

ClimaSys forced vent. roof, 575m³/h, 230V, with roof outlet grille and filter G2, white (RAL 9003)



Main

Range	ClimaSys
Product name	ClimaSys CV
Product or component type	Top hood with fan
Range compatibility	Prisma Prisma P Prisma Prisma PH Prisma Prisma iPM M
Type of filter	G2
Flow rate	Free flow rate: 575 m ³ /h at 50 Hz
Input voltage	230 V 50/60 Hz

Complementary

Absorbed power	85 W
Noise level < at	64 dB
Height	External: 96 mm
Width	External: 340 mm
Depth	External : 340 mm
Cut-out dimensions	228 x 228 mm
Material	Hood: steel
Colour	Hood: signal white (RAL 9003)
IP degree of protection	IP54
Device composition	1 hood: top of enclosure 1 fan 1 fixing elements

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13 cm
Package 1 Width	35 cm
Package 1 Length	35 cm
Package 1 Weight	6.012 kg
Unit Type of Package 2	PAM
Number of Units in Package 2	60
Package 2 Height	125 cm
Package 2 Width	100 cm
Package 2 Length	120 cm
Package 2 Weight	374 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------