

# Product data sheet

## Characteristics

# PFXGP4303TAD

5.7 touch panel display, QVGA, Analog-Single, 2xCOM, ETH, USB A & mini-B, SD, 24VDC, Isolated



### Main

Range of product	Pro-face GP4000
Product or component type	Touch panel screen
Software designation	GP-Pro EX

### Complementary

Display size	5.7 inch
Display type	Colour TFT LCD
Display colour	65536 colours
Display resolution	320 x 240 pixels QVGA
Touch panel	Single touch analogue resistive
Backlight lifespan	50000 hours with white
Brightness	16 levels via touch panel 16 levels by software
Character font	Japanese ASCII Chinese (simplified Chinese) Chinese (traditional Chinese) Korean Cyrillic Thai
[Us] rated supply voltage	24 V DC
Inrush current	30 A
Input voltage limits	19.2...28.8 V DC
Voltage endurance	1000 V AC during 1 min
Local signalling	Status LED green, steady for offline Status LED green, steady for operating status (RUN) Status LED green, flashing for logic stop Status LED orange, flashing for software starting up Status LED red, steady for power ON Status LED red, flashing for ERR (Error)
Maximum power consumption in W	10.5 W 6.5 W when power is not supplied to external devices 4.5 W backlight off (standby mode) 5 W backlight dimmed (brightness: 20%)
Memory description	User data memory 16 MB Backup memory 320 kB

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Integrated connection type	COM1 serial link 1 SUB-D 9-pin male, interface: RS232C, transmission rate: 2400...115200 bps COM2 serial link 1 SUB-D 9-pin female, interface: RS-485 (isolation), transmission rate: 2400...115200 bps COM2 serial link 1 SUB-D 9-pin female, interface: RS-485 (isolation), transmission rate: 187.5 kbps compatible with MPI USB 2.0 type A USB 2.0 type mini B Ethernet 1 RJ45, interface: 10BASE-T/100BASE-TX SD card slot
Electrical connection	Cable 2 mm <sup>2</sup> , AWG 14, max resistance 100 Ohm for functional grounding
Type of cooling	AN (air natural)
Fixing mode	By 4 screws, mounting on 1.6...5 mm thick panel
Cut-out dimensions	156 x 123.5 mm panel cut dimension
Height	137 mm
Width	169.5 mm
Depth	59.5 mm
Net weight	0.8 kg

## Environment

Standards	EN 61000-6-4 IEC 61000-6-2 UL 508 CSA C22.2 No 142 ANSI/ISA 12.12.01 CSA C22.2 No 213 Class I Division 2
Product certifications	UL[RETURN]cUL[RETURN]CE[RETURN]UKCA[RETURN]UKEX[RETURN]KC[RETURN]CCC Ex[RETURN]RCM[RETURN]EAC[RETURN]DNV[RETURN]ABS[RETURN]LR[RETURN]BV[RETURN]
Directives	2014/35/EU - low voltage directive 2014/30/EU - electromagnetic compatibility 2012/19/EU - WEEE directive 2011/65/EU - RoHS 2015/863/EU - RoHS directive
Ambient air temperature for operation	0...55 °C
Ambient air temperature for storage	-20...60 °C
Relative humidity	10...90 % non condensing
Storage Relative Humidity	10...90 % non condensing
Operating altitude	2000 m
IP degree of protection	IP65f (front panel (in enclosure))
NEMA degree of protection	NEMA 4X front panel (in enclosure) NEMA 13 front panel (in enclosure)
Pollution degree	2
Environmental characteristic	Corrosive gas free
Shock resistance	147 m/s <sup>2</sup> (X, Y, Z directions for 3 times) conforming to EN/IEC 61131-2
Vibration resistance	3.5 mm (f = 5...9 Hz) X, Y, Z directions for 10 cycles (approx. 100 min) conforming to EN/IEC 61131-2 9.8 m/s <sup>2</sup> (f = 9...150 Hz) X, Y, Z directions for 10 cycles (approx. 100 min) conforming to EN/IEC 61131-2
Insulation resistance	> 10 MΩ
Electromagnetic compatibility	Electrostatic discharge immunity test - test level: 6 kV (contact discharge) conforming to EN/IEC 61000-4-2 level 3

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14.8 cm
Package 1 Width	18.5 cm
Package 1 Length	23.5 cm
Package 1 Weight	1.107 kg
Unit Type of Package 2	S03
Number of Units in Package 2	4
Package 2 Height	30 cm
Package 2 Width	30 cm

Package 2 Length	40 cm
Package 2 Weight	5.285 kg
Unit Type of Package 3	P06
Number of Units in Package 3	32
Package 3 Height	75 cm
Package 3 Width	60 cm
Package 3 Length	80 cm
Package 3 Weight	51.82 kg

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<input checked="" type="checkbox"/> REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	<input checked="" type="checkbox"/> China RoHS Declaration
RoHS exemption information	<input checked="" type="checkbox"/> Yes