



Main

Range of product	Pro-face SP5000
Product or component type	Touch panel screen

Complementary

Display type	Colour TFT LCD
Display colour	16 million colours
Display resolution	1280 x 800 pixels WXGA
Touch panel	Single touch analogue resistive
Backlight lifespan	50000 hours with white
[Us] rated supply voltage	12...24 V DC
Inrush current	30 A
Input voltage limits	10.8...28.8 V DC
Voltage endurance	1000 V AC during 1 min
Power consumption in W	43 W (max (including box module)) 8.5 W (max (display module only)) 2.5 W (stand by) 5 W
Electrical connection	Cable 2 mm ² , AWG 14, max resistance 100 Ohm for functional grounding
Type of cooling	AN (air natural)
Fixing mode	By 4 screws, mounting on 1.6...5 mm thick panel
Cut-out dimensions	255 x 185 mm panel cut dimension
Height	198.5 mm
Width	268.5 mm
Depth	67 mm
Net weight	2.5 kg

Environment

Standards	UL 61010-2-201 CSA C22.2 No 61010-2-201 ANSI/ISA 12.12.01 CSA C22.2 No 213 Class I Division 2
Product certifications	UL[RETURN]cUL[RETURN]CE[RETURN]UKCA[RETURN]KC[RETURN]RCM[RETURN]PSE[RETURN]
Directives	2014/35/EU - low voltage directive 2014/30/EU - electromagnetic compatibility 2012/19/EU - WEEE directive 2011/65/EU - RoHS 2015/863/EU - RoHS directive 1907/2006/EC - REACH directive 2014/34/EU - ATEX directive 2014/53/EU - radio equipment directive
Ambient air temperature for operation	0...60 °C
Ambient air temperature for storage	-20...60 °C

Relative humidity	10...90 % non-condensing
Storage Relative Humidity	10...90 % non-condensing
Operating altitude	2000 m
IP degree of protection	IP65f
Pollution degree	2
Environmental characteristic	Corrosive gas free
Shock resistance	147 m/s ² (X, Y, Z directions for 10 cycles (approx. 100 min)) conforming to IEC 61131-2
Vibration resistance	3.5 mm constant amplitude (f = 5...9 Hz) X, Y, Z directions for 10 cycles (approx. 100 min) conforming to IEC 61131-2
Insulation resistance	>= 10 MOhm
Electromagnetic compatibility	Electrical fast transient/burst immunity test - test level: 2 kV (power ports) conforming to IEC 61000-4-4

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	20.000 cm
Package 1 Width	33.500 cm
Package 1 Length	37.500 cm
Package 1 Weight	3.777 kg
Unit Type of Package 2	BB1
Number of Units in Package 2	2
Package 2 Height	35.500 cm
Package 2 Width	43.000 cm
Package 2 Length	45.500 cm
Package 2 Weight	8.679 kg
Unit Type of Package 3	P12
Number of Units in Package 3	16
Package 3 Height	99.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	79.680 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes