# PFXYP6MPR42P2

Expansion option, PS6000, 2 x D-Sub 9 pin plug connector, 2,400...115,200 bps



| Main                               |                       |
|------------------------------------|-----------------------|
| Range of product                   | PS6000                |
| Product or component type          | Serial line interface |
| Accessory / separate part category | Connection accessory  |

| Comp | leme | entary |
|------|------|--------|
|------|------|--------|

| Integrated connection type | Mini PCIe with 2 female SUB-D 9 RS422/RS485, transmission rate: 2400115200 bps |
|----------------------------|--|
| Range compatibility        | PS6000   |

## Environment

| Ambient air temperature for operation | 055 °C               |  |
|---------------------------------------|----------------------|--|
| Ambient air temperature for storage   | -3070 °C             |  |
| Relative humidity                     | 595 % non-condensing |  |

#### **Packing Units**

| Unit Type of Package 1       | PCE     |  |
|------------------------------|---------|--|
| Number of Units in Package 1 | 1       |  |
| Package 1 Height             | 4.0 cm  |  |
| Package 1 Width              | 19.0 cm |  |
| Package 1 Length             | 28.0 cm |  |
| Package 1 Weight             | 240.0 g |  |
|                              |         |  |

## Offer Sustainability

| REACh Regulation           | ☑ REACh Declaration  |  |
|----------------------------|--|--|
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) |  |
| China RoHS Regulation      | China RoHS Declaration                                     |  |
| RoHS exemption information | ₫Yes   |  |

## Contractual warranty

| Warranty | 24 months |
|----------|-----------|
|          |           |