

SE8350U0B11

Fan Coil Unit and Zone controller BACnet - rel
humidity - universal output - WH



Main

Device application	Low voltage fan coil
Net weight	340 g
Product or component type	Room controller
Product name	SE8000 Series
Device short name	SE8300
Height	120 mm
AWG gauge	AWG 24...AWG 18
Targeted region	North America.
Directives	2014/30/EU - electromagnetic compatibility 2014/35/EU - low voltage directive 2014/53/EU - radio equipment directive
Humidity measurement drift	Less than 1 % yearly
[In] rated current	4 A
Width	86 mm
Temperature resolution	0.1 °C
Market segment	Lodging/Hotel Small commercial Buildings Healthcare Non-critical buildings Office Residential School
Housing colour	White
Ambient air temperature for storage	-30...50 °C
Depth	25 mm
Ambient air temperature for operation	0...50 °C
Measurement accuracy	Temperature: +/- 0.5 °C, Humidity: +/- 5 %, 20...80 % RH (non-condensing) Humidity: +/- 10 %, 10...20 % (non-condensing) Humidity: +/- 10 %, 80...90 % (non-condensing)
Information displayed	Temperature: - 40...122 °F
Network frequency	50 Hz 60 Hz
Communication port protocol	BACnet MS/TP Modbus RTU
Input voltage	0...10 V DC
Temperature setting range	12...37.5 °C cooling 4.5...32 °C heating
Calibration certificate	1 pt
Output voltage	24 V AC for relay output 0...10 V DC for analog output
Relative humidity	0...95 %
Output current	1 A relay output 3 A relay output (inrush) 0.3 A universal output 1.5 A universal output (inrush)
Input type	2 x dry contact 5 x analog

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Sensor type	10 kOhm T2 NTC thermistor temperature Space RH sensor humidity Bulk polymer humidity
Output type	5 xrelay output 4 xuniversal
[Us] rated supply voltage	24 V AC 50/60 Hz +/- 15 %
Standards	EN/IEC 60730-1 FCC part 15 Subpart B ICES-003 ETSI EN 300 328 ETSI EN 301 489-1:v1.9.2 FCC part 15 Subpart C UL 60730-2-9 ETSI EN 301 489-17:v2.2.1, 2012
Humidity setting range	30...95 %
Range	EcoStruxure Building Expert
Economizer	Yes
Humidity control	Yes
PIR cover	No
Scheduling	No

Complementary

Surface treatment	Untreated
Surface finish	Matt
Function available	Fan control HVAC control Available with CO2/RH/T Brightness sensor Changes can be made directly over display Code lock function Easily configurable Firmware update by USB

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	30.5 cm
Package 1 Width	21.8 cm
Package 1 Length	6.4 cm
Package 1 Weight	242 g

Offer Sustainability

REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes