



Main

| | |
|---------------------------|-------------|
| Range compatibility | PacDrive 3 |
| Device short name | SH3.....P |
| Product or component type | Servo motor |

Complementary

| | |
|---------------------------|--|
| Maximum mechanical speed | 6000 rpm |
| [Us] rated supply voltage | 115...480 V |
| Network number of phases | Three phase |
| Continuous stall current | 4.8 A |
| Continuous stall torque | 5.8 N.m at 115...480 V three phase |
| Continuous power | 1900 W |
| Peak stall torque | 18.3 N.m at 115...480 V three phase |
| Nominal output power | 580 W at 115 V single phase 1090 W at 230 V single phase 1930 W at 400 V three phase 2210 W at 480 V three phase |
| Nominal torque | 5.5 N.M at 115 V single phase 5.2 N.M at 230 V single phase 4.6 N.M at 400 V three phase 4.4 N.m at 480 V three phase |
| Nominal speed | 1000 rpm at 115 V single phase 2000 rpm at 230 V single phase 4000 rpm at 400 V three phase 4800 rpm at 480 V three phase |
| Maximum current Irms | 17.1 A |
| Shaft end | Parallel key |
| Shaft diameter | 19 mm |
| Shaft length | 40 mm |
| Key width | 6 mm |
| IP degree of protection | IP54 shaft bushing without shaft seal ring: conforming to EN/IEC 60034-5 IP65 motor: conforming to EN/IEC 60034-5 IP65 shaft bushing: conforming to EN/IEC 60034-5 |
| Encoder type | Absolute single turn SinCos Hiperface |
| Speed feedback resolution | 128 periods |
| Holding brake | Without |
| Mounting support | International standard flange |
| Motor flange size | 100 mm |
| Electrical connection | Rotatable right angled connector |
| Torque constant | 1.21 N.m/A at 120 °C |
| Back emf constant | 77 V/krpm at 20 °C |

| | |
|---------------------------------------|--|
| Number of motor poles | 4 |
| Rotor inertia | 2.31 kg.cm ² |
| Stator resistance | 2.4 Ohm |
| Stator inductance | 19.5 mH |
| Maximum radial force Fr | 990 N at 1000 rpm 790 N at 2000 rpm 690 N at 3000 rpm 620 N at 4000 rpm |
| Maximum axial force Fa | 160 N |
| Type of cooling | Natural convection |
| Length | 204.5 mm |
| Centring collar diameter | 95 mm |
| Centring collar depth | 3.5 mm |
| Number of mounting holes | 4 |
| Mounting holes diameter | 9.0 mm |
| Circle diameter of the mounting holes | 115 mm |
| Net weight | 5.8 kg |

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 30.0 cm |
| Package 1 Width | 30.0 cm |
| Package 1 Length | 40.0 cm |
| Package 1 Weight | 6.6 kg |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| PVC free | Yes |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|