

SLASXXX

SmartX Temperature Sensor, Resistive 10K
Type 3 Thermistor, Blank, with Matte White
Cover



Main

Product or component type	Sensor
Type of measurement	Temperature
Device application	HVAC Temperature control
Flame retardance	UL94-V0
IP degree of protection	IP20
Location	Living space
Depth	24 mm
Height	115 mm
Width	85 mm
Standards	UL 916 FCC part 15 class B
Colour	White
Ambient air temperature for operation	0...50 °C
Relative humidity	0...95 %
Sensor type	10 kOhm T3 thermistor
Surface finish	Matt
Product name	SmartX Living Space Sensor
Range	SpaceLogic

Complementary

Device presentation	Complete product
Connections - terminals	Screw - 2 cable(s) (AWG 24...AWG 18)
Range compatibility	EcoStruxure Building Operation SmartX Room Purpose Controller programmable controllers
Material	ABS (acrylonitrile butadiene-styrene)
Display type	Without display
Communication port protocol	- - 2 wires

Environment

Measurement range	0...50 °C temperature
Product certifications	CE conforming to EN 61000-6-3[RETURN]RCM[RETURN]EAC[RETURN]ICES-003

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.800 cm
Package 1 Width	9.700 cm
Package 1 Length	14.200 cm
Package 1 Weight	138.000 g
Unit Type of Package 2	S03
Number of Units in Package 2	20

Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	3.248 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins