

Product data sheet

Characteristics

SMT3000IC

APC Smart-UPS, Line Interactive, 3kVA, Tower, 230V, 8x IEC C13+2x IEC C19 outlets, SmartConnect Port+SmartSlot, AVR, LCD



Overview

| | |
|--------------|---|
| Presentation | Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices. |
| Lead time | Usually in Stock |

Main

| | |
|---------------------------|--|
| Main Input Voltage | 230 V |
| Other Input Voltage | 220 V 240 V |
| Main Output Voltage | 230 V |
| Other Output Voltage | 220 V 240 V |
| Rated power in W | 2700 W |
| Rated power in VA | 3000 VA |
| Product or component type | Uninterruptible power supply (UPS) |
| Input Connection Type | IEC 320 C20 Schuko CEE 7 / EU1-16P BS1363A British |
| Output connection type | 8 IEC 320 C13 2 IEC Jumpers 1 IEC 320 C19 |
| Number of rack unit | 0U |
| Number of cables | 1 |
| Battery type | Lead-acid battery |
| Provided equipment | USB cable |

Complementary

| | |
|------------------|---|
| Software package | SmartConnect software for remote power monitoring feature availability varies by terms of use |
|------------------|---|

Batteries & Runtime

| | |
|--|--|
| Additional information | Configurable for 220 : 230 or 240 nominal output voltage |
| Extended runtime | 1 |
| Number of battery filled slots | 0 |
| Number of battery free slots | 0 |
| Battery recharge time | 3 h |
| Number of battery replacement quantity | 1 |
| Battery life | 3...5 year(s) |
| Battery charger power | 271 W rated |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

General

| | |
|-------------------------------------|--------------------------|
| Number of power module filled slots | 0 |
| Number of power module free slots | 0 |
| Product web sub-family | Cloud-enabled monitoring |
| Redundant | No |

Physical

| | |
|---------------------|--------------------|
| Colour | Black |
| Height | 43.5 cm |
| Width | 19.7 cm |
| Depth | 54.4 cm |
| Net weight | 52.5 kg |
| Mounting location | Front |
| Mounting preference | No preference |
| Mounting mode | Not rack-mountable |
| Two post mountable | 0 |
| USB compatible | Yes |

Input

| | |
|----------------------|---------------------------------------|
| Input voltage limits | 151...302 V adjustable 160...286 V |
| Network frequency | 50/60 Hz +/- 3 Hz auto-sensing |

Output

| | |
|----------------------------------|---------------------------------|
| Harmonic distortion | Less than 5 % |
| Maximum configurable power in VA | 3000 VA |
| Maximum configurable power in W | 2700 W |
| Transfer time | 6 ms typical : 10 ms maximum |
| UPS type | Line interactive |
| Wave type | Sine wave |
| Output frequency | 50/60 Hz +/- 3 Hz sync to mains |

Conformance

| | |
|------------------------|--|
| Product certifications | CE[RETURN]EAC[RETURN]RCM[RETURN]VDE |
| Standards | EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018 |

Environmental

| | |
|---------------------------------------|-------------------|
| Acoustic level | 53 dBA |
| Heat dissipation | 375 Btu/h |
| Operating altitude | 0...10000 ft |
| Ambient air temperature for operation | 0...40 °C |
| Ambient air temperature for storage | -15...45 °C |
| Storage altitude | 0.00...15240.00 m |
| Relative humidity | 0...95 % |
| Storage Relative Humidity | 0...95 % |

Communications & Management

| | |
|----------------------------|--|
| Control panel | Multifunction LCD status and control console |
| Emergency power off | Yes |
| Free slots | 1 |
| Communication port support | SmartConnect Ethernet port: for cloud monitoring feature availability varies by terms of use |
| Alarm | Alarm when on battery : distinctive low battery alarm : configurable delays |

Surge Protection and Filtering

| | |
|-------------------|--|
| Surge energy rate | 365 J |
| Noise suppression | Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449 |

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 69.9 cm |
| Package 1 Width | 76.2 cm |
| Package 1 Length | 38.1 cm |
| Package 1 Weight | 63.7 kg |

Offer Sustainability

| | |
|-----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation |  REACH Declaration |
| EU RoHS Directive | Compliant with Exemptions |
| China RoHS Regulation |  China RoHS Declaration |
| RoHS exemption information |  Yes |
| Environmental Disclosure |  Product Environmental Profile |
| Circularity Profile |  End Of Life Information |
| Optimized Energy Efficiency | Energy efficient product |
| Take-back | Take-back program available |

Contractual warranty

| | |
|----------|--|
| Warranty | 3 years repair or replace (excluding battery) and 2 years for battery, optional on-site warranties available, optional extended warranties available |
|----------|--|