

Product data sheet

Characteristics

SMX120BP

APC Smart-UPS X-Series External Battery

Pack Rack/Tower 120V, 1200VAh, rackmount,
4U



Overview

Lead time

Usually Ships within 2 Weeks



Main

Product or component type	Battery
Number of rack unit	4U
Battery type	Lead-acid battery
Provided equipment	Installation guide Rack mounting brackets

Batteries & Runtime

Number of battery blocks per string	10
Device mounting	Enclosed battery cartridge
Number of battery filled slots	0
Number of battery free slots	0
Number of battery replacement quantity	2
Battery voltage	120 V

Physical

Colour	Black
Height	43.2 cm
Width	17.8 cm
Depth	48.3 cm
Net weight	60.91 kg
Mounting mode	Rack-mounted

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	33 cm
Package 1 Width	58.6 cm
Package 1 Length	63.3 cm
Package 1 Weight	65.45 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------