

Product data sheet

Characteristics

SMX48RMBP2U

APC Smart-UPS X-Series External Battery Pack Rack/Tower 48V, 864VAh, rackmount, 2U



Overview

Lead time	Usually Ships within 2 Weeks
-----------	------------------------------



Main

Main Input Voltage	48 V DC
Product or component type	Battery
Number of rack unit	2U
Battery type	Lead-acid battery
Provided equipment	Installation guide Rack mounting brackets

Batteries & Runtime

Device mounting	Enclosed battery cartridge
Number of battery filled slots	0
Number of battery free slots	0
Number of battery replacement quantity	2
Battery voltage	48 V

Physical

Colour	Black
Height	8.9 cm
Width	43.2 cm
Depth	49 cm
Net weight	28.64 kg
Mounting mode	Rack-mounted

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.6 cm
Package 1 Width	58.9 cm
Package 1 Length	62 cm
Package 1 Weight	35.5 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	8
Package 2 Height	115 cm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Package 2 Width	100 cm
Package 2 Length	120 cm
Package 2 Weight	283.408 kg
SCC14	731304268611

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
Take-back	Take-back program available

Contractual warranty

Warranty	2 anni con riparazione o sostituzione
----------	---------------------------------------