

Product data sheet

Characteristics

SRT192RMBP

APC Smart-UPS SRT 192V 5kVA and 6kVA RM Battery Pack



Overview

Lead time	Usually in Stock
-----------	------------------



Main

Product or component type	Battery
Number of rack unit	3U
Battery type	Lead-acid battery
Provided equipment	Installation guide Warranty card

Batteries & Runtime

Number of battery free slots	0
Number of battery filled slots	0
Device mounting	Stand alone battery stack
Battery voltage	192 V
Number of battery replacement quantity	2

Physical

Colour	Black
Height	13 cm
Width	43.2 cm
Depth	68.27 cm
Net weight	91 kg
Mounting mode	Rack-mounted

Conformance

Standards	OSHPD
-----------	-------

Environmental

Ambient air temperature for operation	0...40 °C
Operating altitude	0...10000 ft
Relative humidity	0...95 % non-condensing
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.00...15240.00 m
Storage Relative Humidity	0...95 % non-condensing

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	42 cm
Package 1 Width	60 cm
Package 1 Length	100 cm
Package 1 Weight	105.5 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------