

SRT3000RMXLI-NC

APC Smart-UPS On-Line, 3kVA, Rackmount
2U, 230V, 8x C13+2x C19 IEC outlets, Network
Card, Extended runtime, W/ rail kit



Overview

Presentation	High density, double-conversion on-line power protection with scalable runtime.
Lead time	Usually in Stock

Main

Main Input Voltage	230 V
Product or component type	Uninterruptible power supply (UPS)
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated power in W	2700 W
Rated power in VA	3000 VA
Input Connection Type	BS1363A British IEC 60320 C20 Schuko CEE 7 / EU1-16P
Output connection type	8 IEC 60320 C13 2 IEC Jumpers 2 IEC 60320 C19
Number of rack unit	2U
Cable length	2.44 m
Number of cables	1
Provided equipment	CD with software Documentation CD Installation guide Network management card Rack mounting brackets Rack mounting support rails USB cable Warranty card

Batteries & Runtime

Battery type	Lead-acid battery
Number of battery filled slots	1
Battery recharge time	3 h
Number of battery replacement quantity	1
Battery voltage	96 V
Battery charger power	168 W rated

Battery life	3...5 year(s)
Extended runtime	1

General

UPS type	Double conversion online
Product web sub-family	High density
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Colour	Black
Height	8.5 cm
Width	43.2 cm
Depth	63.5 cm
Net weight	31.3 kg
Mounting location	Front
Mounting preference	Lower
Mounting mode	Rack-mounted
Two post mountable	0
USB compatible	Yes
Mounting position	Horizontal

Input

Network frequency	40...70 Hz auto-sensing
Input voltage limits	100...275 V adjustable (half load)

Output

Maximum configurable power in VA	3000 VA
Maximum configurable power in W	2700 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Wave type	Sine wave
Harmonic distortion	Less than 2 %
Crest factor	3 : 1
Bypass type	Internal bypass (automatic and manual)
Additional information	Configurable for 220 : 230 or 240 nominal output voltage

Conformance

Product certifications	CE[RETURN]EAC[RETURN]RCM[RETURN]VDE
Marking	CE Mark
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0.00...15240.00 m
Acoustic level	55 dBA
Heat dissipation	703 Btu/h
IP degree of protection	IP20

Communications & Management

Free slots	0
Preinstalled device	Network management card 3 with environmental monitoring
Alarm	Audible and visible alarms : prioritized by severity
Emergency power off	Yes

Surge Protection and Filtering

Surge energy rate	340 J
-------------------	-------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.6 cm
Package 1 Width	87.1 cm
Package 1 Length	59.9 cm
Package 1 Weight	39.92 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Lead free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery
----------	---