

# Product data sheet

## Characteristics

# SRT6KRMXLIM

APC Smart-UPS On-Line, 6kVA/6kW, Rackmount 4U, 230V, 6x C13+4x C19 IEC outlets, Network Card+SmartSlot, Extended runtime, W/ rail kit, Marine



### Overview

Presentation	High availability, ruggedized power protection for shipboard and other transportation applications.
Lead time	Usually in Stock

### Main

Main Input Voltage	230 V
Product or component type	Uninterruptible power supply (UPS)
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated power in W	6000 W
Rated power in VA	6000 VA
Output connection type	6 IEC 60320 C13 2 IEC Jumpers 4 IEC 60320 C19
Output connector type	Hard wire 3-wire (H N + E) 1
Number of rack unit	4U
Provided equipment	CD with software Installation guide Rack mounting hardware Rack mounting brackets Rack mounting support rails Temperature probe USB cable Warranty card

### Batteries & Runtime

Battery type	Lead-acid battery
Number of battery filled slots	0
Battery recharge time	1 h
Number of battery replacement quantity	1
Battery charger power	893 W rated
Battery life	3...5 year(s)
Extended runtime	1

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## General

UPS type	Double conversion online
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

## Physical

Colour	Black
Height	17.4 cm
Width	43.2 cm
Depth	71.94 cm
Net weight	60 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Rack-mounted
Two post mountable	0
USB compatible	Yes

## Input

Network frequency	40...70 Hz auto-sensing
Number of input connectors	1 hard wire 3-wire (1P + N + E)

## Output

Maximum configurable power in VA	6000 VA
Maximum configurable power in W	6000 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Wave type	Sine wave
Harmonic distortion	Less than 3 %
Crest factor	3 : 1
Bypass type	Internal bypass (automatic and manual)

## Conformance

Product certifications	CE[RETURN]EAC[RETURN]RCM[RETURN]VDE
Marking	CE Mark
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0.00...15240.00 m
Acoustic level	55 dBA
Heat dissipation	1300 Btu/h
IP degree of protection	IP20

## Communications & Management

Free slots	0
Preinstalled device	Dry contact I/O smartslot card
Alarm	Audible and visible alarms : prioritized by severity
Emergency power off	Yes

## Surge Protection and Filtering

Surge energy rate	480 J
-------------------	-------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	37 cm
Package 1 Width	96 cm
Package 1 Length	61 cm
Package 1 Weight	67 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<input checked="" type="checkbox"/> <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
China RoHS Regulation	<input checked="" type="checkbox"/> <a href="#">China RoHS Declaration</a>
RoHS exemption information	<input checked="" type="checkbox"/> Yes
Environmental Disclosure	<input checked="" type="checkbox"/> <a href="#">Product Environmental Profile</a>
Circularity Profile	<input checked="" type="checkbox"/> <a href="#">End Of Life Information</a>
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

## Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery
----------	---