

SRTL1000RMXLI

APC Smart-UPS On-Line, 1000VA, Rackmount
3U, 230V, 8x C13 IEC outlets, SmartSlot,
Extended runtime, W/ rail kit, W/ Lithium-ion
external battery



Overview

Presentation	High density, double-conversion on-line power protection with scalable runtime.
Lead time	Usually in Stock

Main

Main Input Voltage	230 V
Product or component type	Uninterruptible power supply (UPS)
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated power in W	900 W
Rated power in VA	1000 VA
Input Connection Type	IEC 60320 C14
Output connection type	8 IEC 60320 C13
Number of rack unit	3U
Cable length	1.83 m
Number of cables	1
Provided equipment	CD with software Communication cable Documentation CD Installation guide Removable support feet USB cable Warranty card

Batteries & Runtime

Battery type	Li-Ion (Lithium-Ion)
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	6 h
Battery voltage	48 V
Battery charger power	103 W rated
Battery life	5...10 year(s)
Extended runtime	1

General

UPS type	Double conversion online
Product web sub-family	Lithium-Ion
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Colour	Black with silver front bezel
Height	8.5 cm
Width	43.2 cm
Depth	56 cm
Net weight	13.7 kg
Mounting preference	No preference
Mounting mode	Rack-mounted with kit
Two post mountable	0
USB compatible	Yes
Mounting position	Horizontal Vertical

Input

Network frequency	40...70 Hz auto-sensing
Input voltage limits	160...275 V 40% load 80...150 V

Output

Maximum configurable power in VA	1000 VA
Maximum configurable power in W	900 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Wave type	Sine wave
Harmonic distortion	Less than 2 %
Crest factor	3 : 1
Bypass type	Built-in bypass

Conformance

Product certifications	CE[RETURN]EAC[RETURN]RCM[RETURN]VDE
Marking	CE Mark
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0.00...15240.00 m
Acoustic level	50 dBA
Heat dissipation	400 Btu/h
IP degree of protection	IP20

Communications & Management

Free slots	1
Alarm	Audible and visible alarms : prioritized by severity
Emergency power off	Yes

Surge Protection and Filtering

Surge energy rate	340 J
-------------------	-------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.5 cm
Package 1 Width	60 cm
Package 1 Length	81 cm
Package 1 Weight	21 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	5 year repair or replace
----------	--------------------------