



Overview

Lead time	Usually in Stock
-----------	------------------



Main

Product or component type	Battery
Number of rack unit	3U
Battery type	Lead-acid battery
Provided equipment	User manual Rack mounting brackets Battery cable

Batteries & Runtime

Number of battery blocks per string	20
Device mounting	Rack mount
Number of battery filled slots	0
Number of battery free slots	0
Battery voltage	240 V

Physical

Colour	Black
Height	13.3 cm
Width	43.8 cm
Depth	61.5 cm
Net weight	63 kg
Mounting mode	Rack-mounted with kit
USB compatible	No

Conformance

Product certifications	CE[RETURN]UKCA[RETURN]EAC[RETURN]EN/IEC 62040-1
------------------------	---

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3000 m
Ambient air temperature for storage	-15...40 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0...15000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	25.000 cm
Package 1 Width	58.000 cm
Package 1 Length	87.000 cm
Package 1 Weight	69.839 kg
Unit Type of Package 2	P12
Number of Units in Package 2	6
Package 2 Height	75.000 cm
Package 2 Width	80.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	431.000 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------