



Overview

Presentation	High availability, ruggedized power protection for shipboard and other transportation applications.
Lead time	Usually in Stock

Main

Main Input Voltage	230 V
Product or component type	Filter
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated power in W	700 W
Rated power in VA	1000 VA
Input Connection Type	IEC 60320 C14
Output connection type	6 IEC 60320 2 IEC Jumpers
Number of rack unit	2U
Cable length	2.50 m
Number of cables	1
Provided equipment	CD with software Relay board Smart UPS signalling RS-232 cable User manual

Batteries & Runtime

Battery type	Lead-acid battery
Number of battery filled slots	1
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	1
Battery charger power	109 W rated
Battery life	3...5 year(s)
Extended runtime	1

General

UPS type	Double conversion online
Number of power module	700
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
Variant option	Shipboard

Physical

Colour	Black
Height	43.2 cm
Width	8.5 cm
Depth	48.3 cm
Net weight	23 kg
Mounting location	Front
Mounting preference	Lower
Mounting mode	Rack-mounted
Two post mountable	0
USB compatible	No

Input

Network frequency	50/60 Hz +/- 5 Hz auto-sensing
Input voltage limits	180...280 V
Input Power Factor at Full Load	1

Output

Maximum configurable power in VA	1000 VA
Maximum configurable power in W	700 W
Output frequency	50/60 Hz +/- 3 Hz user adjustable +/- 0.1 Hz sync to mains 60 Hz +/- 0.1 % for 60 Hz nominal unsynchronised 50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised
Wave type	Sine wave
Efficiency	88 % (full load)
Harmonic distortion	Less than 3 %
Crest factor	3 : 1
Bypass type	Built-in bypass
Additional information	Configurable for 220 : 230 or 240 nominal output voltage

Conformance

Product certifications	CE[RETURN]DNV[RETURN]KCC
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Ambient air temperature for operation	0...55 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient air temperature for storage	-20...50 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0.00...15240.00 m
Acoustic level	55 dBA
Heat dissipation	324 Btu/h
IP degree of protection	IP20

Communications & Management

Free slots	0
Preinstalled device	Dry contact I/O smartslot card
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Emergency power off	Optional

Surge Protection and Filtering

Surge energy rate	420 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	28.6 cm
Package 1 Width	63 cm
Package 1 Length	59.4 cm
Package 1 Weight	27.8 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace, optional on-site warranties available, optional extended warranties available
----------	--