



Overview

Lead time	Usually in Stock
-----------	------------------

Main

Product or component type	Battery
Number of rack unit	3U
Number of cables	1.0
Battery type	Lead-acid battery
Provided equipment	Installation guide Rack mounting brackets User manual

Batteries & Runtime

Number of battery blocks per string	16
Number of battery free slots	0
Number of battery filled slots	4
Device mounting	Stand alone battery stack
Battery voltage	192 V
Additional information	Replace all batteries in operation together (UPS internal and external batteries) all-at-once
Number of battery replacement quantity	2

Physical

Colour	Black
Height	13 cm
Width	43.2 cm
Depth	66 cm
Net weight	90.91 kg
Mounting mode	Rack-mounted

Environmental

Ambient air temperature for operation	0...40 °C
Operating altitude	0...10000 ft
Relative humidity	0...95 % non-condensing
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.00...15240.00 m
Storage Relative Humidity	0...95 % non-condensing

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the company mentioned herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	41.3 cm
Package 1 Width	100 cm
Package 1 Length	60 cm
Package 1 Weight	101.36 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace, optional on-site warranties available, optional extended warranties available
----------	--