

SURT3000XLIX554

APC Smart-UPS RT 3000VA, 230V, 8x IEC 60320 C13 & 3x IEC Jumpers & 2x IEC 60320 C19



Overview

Presentation	High density, double-conversion on-line power protection with scalable runtime.
Lead time	Usually in Stock

Main

Main Input Voltage	230 V
Product or component type	Uninterruptible power supply (UPS)
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated power in W	2100 W
Rated power in VA	3000 VA
Input Connection Type	BS1363A British IEC 60320 C20
Output connection type	8 IEC 60320 C13 3 IEC Jumpers 2 IEC 60320 C19
Number of rack unit	6U
Cable length	2.44 m
Provided equipment	CD with software Service manual Smart UPS signalling RS-232 cable User manual

Batteries & Runtime

Battery type	Lead-acid battery
Number of battery free slots	0
Battery recharge time	2.5 h
Number of battery replacement quantity	2
Battery charger power	382 W rated
Extended runtime	1

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

General

UPS type	Double conversion online
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Colour	Black
Height	43.2 cm
Width	13 cm
Depth	66 cm
Net weight	54.55 kg
Mounting location	Front
Mounting preference	Lower
Mounting mode	Rack-mounted with kit
Two post mountable	0
USB compatible	No

Input

Network frequency	40...70 Hz auto-sensing
Input voltage limits	160...280 V
Switching current capacity	125 A

Output

Maximum configurable power in VA	3000 VA
Maximum configurable power in W	2100 W
Output frequency	50/60 Hz +/- 3 Hz user adjustable +/- 0.1 Hz sync to mains
Wave type	Sine wave
Efficiency	92 % (full load)
Harmonic distortion	Less than 3 %
Crest factor	3 : 1
Bypass type	Internal bypass (automatic and manual)
Additional information	Configurable for 220 : 230 or 240 nominal output voltage

Conformance

Product certifications	GOST[RETURN]VDE
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m
Acoustic level	55 dBA
Heat dissipation	609 Btu/h

Communications & Management

Free slots	0
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Emergency power off	Yes

Surge Protection and Filtering

Surge energy rate	480 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	34.7 cm
Package 1 Width	98 cm
Package 1 Length	60.3 cm
Package 1 Weight	63.64 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------