



Overview

Lead time	Usually in Stock
-----------	------------------



Main

Product or component type	Battery
Number of rack unit	2U
Battery type	Lead-acid battery
Provided equipment	Installation guide Rack mounting brackets User manual

Batteries & Runtime

Number of battery free slots	0
Number of battery filled slots	2
Device mounting	Stand alone battery stack
Battery voltage	48 V
Additional information	Replace all batteries in operation together (UPS internal and external batteries) all-at-once
Number of battery replacement quantity	2

Physical

Colour	Black
Height	8.5 cm
Width	43.2 cm
Depth	48.3 cm
Net weight	29.56 kg
Mounting mode	Rack-mounted

Environmental

Ambient air temperature for operation	0...40 °C
Operating altitude	0...10000 ft
Relative humidity	0...95 % non-condensing
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.00...15240.00 m
Storage Relative Humidity	0...95 % non-condensing

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	28.6 cm
Package 1 Width	59.4 cm
Package 1 Length	63 cm
Package 1 Weight	32.28 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace, optional on-site warranties available, optional extended warranties available
----------	--