

SXWADWIFI10001

Wi-Fi card, SpaceLogic HMI, optional, for SpaceLogic HMI Advanced Display v3



Main

Provided equipment	Wi-Fi module Wi-Fi antenna
Width	22 mm
Product or component type	Communication module
Ambient air temperature for storage	-40...85 °C
Range	SpaceLogic
Ambient air temperature for operation	0...70 °C
Fixing mode	Adhesive tape Insertion into a M.2 connector
Relative humidity	15...95 % RH, non-condensing
Standards	EN 301-489-1:v1.9.2 EN 301-489-17:v2.2.1 FCC CFR 47 part 15 Subpart B class B FCC Part 15 Subpart C 15.247 RSS 210:2010 Annexe 8 ETSI EN 300 328:v2.1.1
Operating distance	40 m in open air
Communication network type	Wi-Fi IEEE 802.11 b/g/n at 2.4 GHz

Complementary

Range compatibility	SpaceLogic SmartX HMI Advanced Display v3
Product certifications	CE[RETURN]ANATEL[RETURN]IC[RETURN]FCC[RETURN]CofeteI[RETURN]RCM[RETURN]PORN

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.4 cm
Package 1 Width	13.8 cm
Package 1 Length	16 cm
Package 1 Weight	160 g

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
RoHS exemption information	Yes

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.