

SXWASPSBX10002

SpaceLogic automation server, AS-P-NLS, 2 RS-485 ports, 2 10/100 ethernet ports, secure boot



Main

Product or component type	Network controller
Network frequency	50 Hz 60 Hz 60 Hz
Backup time	10 days
Communication service	TLS 1.0
Net weight	0.321 kg
Width	90 mm
Mounting mode	DIN rail mount
Device short name	AS-P-NLS
Product certifications	BTL B-BC[RETURN]cUL listed[RETURN]UL listed[RETURN]RCM[RETURN]cUL listed[RETURN]UL listed[RETURN]RCM
Maximum power consumption in W	10 W
Height	114 mm
Model	AS-P-NLS
Colour	Black
Ambient air temperature for storage	-20...70 °C
Depth	64 mm
Clock drift	+/- 52 s/month
Flame retardance	UL94-5VB
Ambient air temperature for operation	0...50 °C
IP degree of protection	IP20
Standards	EN 61000-6-2 EN 50491-5-3 EN 60730-1 EN 60730-2-11 EN 50491-3 UL 916 EN 50491-1 EN 61000-6-3 EN 50491-5-2 FCC part 15 Subpart B class B
[Us] rated supply voltage	24 V AC 24 V DC
Number of port	2, connector type: RJ45 1, connector type: USB device port Mini-B 1, connector type: USB host port type A 2 RS485
Communication port support	ETHERNET 10/100BASE-TX
Memory type	4 GB flash 512 MB RAM
Maximum number of connected devices	464

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Complementary

Communication port protocol	BACnet HTTP HTTPS Modbus TCP serial line master or slave TCP (Transmission Control Protocol)
-----------------------------	--

Environment

Relative humidity	0...95 % (RH, non-condensing)
-------------------	-------------------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9 cm
Package 1 Width	11.4 cm
Package 1 Length	6.4 cm
Package 1 Weight	321 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes
Halogen content performance	Halogen free plastic parts & cables product