SXWASPXXX10001

Automation server, SpaceLogic, AS-P, LonWorks, 2 RS-485 ports, 2 10/100 ethernet ports





Main Produ

Product or component type	Controller
Communication service	SNMP network management SMTP e-mail notification SMTPS e-mail notification Modbus TCP client Modbus TCP server
Current consumption	400 mA
Flame retardance	UL94V0-5VB
Width	90 mm
Product certifications	BTL[RETURN]CE[RETURN]cULus[RETURN]FCC part 15 class B[RETURN]ICES-003
Net weight	321 g
Device short name	AS-P
Height	114 mm
Ambient air temperature for storage	-2070 °C
Depth	64 mm
Ambient air temperature for operation	050 °C
IP degree of protection	IP20
Standards	UL 94 UL 916 FCC CFR 47 part 15
Memory type	512 MB RAM 4 GB flash
Product brand	Schneider Electric
Range	EcoStruxure Building Operation

Complementary

Complementary	APO/PO	
Material	ABS/PC	
Product mounting	On base	
	DIN rail	
Web services	TLS 1.0	
	HTTP server	
	Programmable scripts: alarm summaries, report management	
I/O limit processor capacity	464 I/O, 29 modules	
Range compatibility	EcoStruxure Building Operation TB-ASP-W1 terminal base	
	EcoStruxure Building Operation TB-AS-W1 terminal base	
Processor name	Spear 320s	
Communication port protocol	BACnet	
	Modbus TCP master RS485	
	Modbus TCP slave RS485	
	HTTPS RJ45	
	HTTP RJ45	
	LON TP/FT-10	
Integrated connection type	USB 2.0 type A	
	USB type mini B	

Environment

Relative humidity 0...95 %

Packing Units

3	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.7 cm
Package 1 Width	5.7 cm
Package 1 Length	9.1 cm
Package 1 Weight	271.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	36
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	10.513 kg

Offer Sustainability

- · · · · ·	
Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	[™] China RoHS Declaration
RoHS exemption information	€Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes
Halogen content performance	Halogen free plastic parts & cables product