

Product data sheet

Characteristics

SXWDOA12X10001

Central I/O module, SpaceLogic, 12 Form A digital outputs



Main

| | |
|---------------------------------------|--|
| Net weight | 194 g |
| Product or component type | I/O module |
| Device short name | DO-FA-12 |
| Height | 114 mm |
| Flame retardance | UL94V0-5VB |
| Width | 30 mm |
| Product certifications | ICES-003[RETURN]FCC part 15 class B[RETURN]CE[RETURN]RCM |
| Power consumption in VA | 1.8 W |
| Ambient air temperature for storage | -20...70 °C |
| Depth | 64 mm |
| Ambient air temperature for operation | 0...50 °C |
| IP degree of protection | IP20 |
| Relative humidity | 0...95 % non-condensing |
| Product name | I/O Modules |
| Product brand | Schneider Electric |
| Range | EcoStruxure Building Operation |

Complementary

| | |
|------------------------|---|
| Electrical connection | Plug-in sub-base |
| Control type | Without |
| Discrete output number | 12 |
| Discrete input voltage | 24 V |
| Mounting support | DIN rail Wall |
| Discrete output type | Relay |
| Local signalling | LED (green) for relay energised |
| Range compatibility | EcoStruxure Building Operation TB-IO-W1 terminal base |
| Standards | UL 864 UL 916 FCC CFR 47 part 15 |
| Material | ABS + PC |

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 9.0 cm |
| Package 1 Width | 5.7 cm |
| Package 1 Length | 11.8 cm |
| Package 1 Weight | 196.2 g |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

| | |
|-----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation |  REACH Declaration |
| EU RoHS Directive | Compliant with Exemptions |
| Mercury free | Yes |
| China RoHS Regulation |  China RoHS Declaration |
| RoHS exemption information |  Yes |
| Environmental Disclosure |  Product Environmental Profile |
| Circularity Profile |  End Of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| PVC free | Yes |
| Halogen content performance | Halogen free plastic parts & cables product |