

SXWIPIOBA10001

Input/output expander, SpaceLogic IP-IO
Series, 10 universal inputs/outputs



Main

Product or component type	I/O module
Device short name	IP-IO-UIO10
Height	110 mm
Model	IP-IO-UIO10
Network frequency	50 Hz 60 Hz
Backup time	7 days
Width	153 mm
Mounting mode	DIN rail mount Panel-mounted
Maximum power consumption in W	9 W
Power consumption in VA	17 VA
Ambient air temperature for storage	-20...70 °C
Ambient air temperature for operation	0...50 °C
Input/output type	10 universal I/O
Number of port	2, connector type: RJ45 1, connector type: USB type A female 1, connector type: USB device port Mini-B
Relative humidity	0...95 % RH, non-condensing
Memory type	32 MB flash 128 MB RAM
Communication port support	ETHERNET 10/100BASE-TX
[Us] rated supply voltage	24 V AC +/- 20 % 24...30 V DC 21...33 V DC
Communication port protocol	BACnet IP

Complementary

Standards	CAN/CSA C22.2 No. 24
-----------	----------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.0 cm
Package 1 Width	12.4 cm
Package 1 Length	16.3 cm
Package 1 Weight	417.0 g

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes
Halogen content performance	Halogen free plastic parts product