

SXWIIPIOCA10001

Input/output expander, SpaceLogic IP-IO Series, 5 universal inputs/outputs, 4 digital output form A relay



Main

Product or component type	I/O module
Device short name	IP-IO-UIO5DOFA4
Height	110 mm
Model	IP-IO-UIO5DOFA4
Network frequency	50 Hz 60 Hz
Backup time	7 days
Width	153 mm
Mounting mode	DIN rail mount Panel-mounted
Maximum power consumption in W	9 W
Power consumption in VA	17 VA
Ambient air temperature for storage	-20...70 °C
Ambient air temperature for operation	0...50 °C
Input/output type	5 universal I/O
Number of port	2, connector type: RJ45 1, connector type: USB type A female 1, connector type: USB device port Mini-B
Relative humidity	0...95 % RH, non-condensing
Number of outputs	3 form A relay output 1 form A relay output 3
Memory type	32 MB flash 128 MB RAM
Communication port support	ETHERNET 10/100BASE-TX
[Us] rated supply voltage	24 V AC +/- 20 % 24...30 V DC 21...33 V DC
Communication port protocol	BACnet IP

Complementary

Standards	CAN/CSA C22.2 No. 24
-----------	----------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.0 cm
Package 1 Width	12.4 cm
Package 1 Length	16.3 cm
Package 1 Weight	417.0 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes
Halogen content performance	Halogen free plastic parts product