

SXWRCF12BM10001

Controller, EasyLogic, RP-C, BACnet MS/TP, 8 universal input/output, 3 relay form A outputs, 1 high power relay output



Main

Device application	Low voltage fan coil Chilled beam
Product or component type	Field controller
Device short name	RP-C-12B-M-24V
Function available	Programmable Smart sensor input
Topology	Daisy chain
Model	RP-C-F12B-M
Colour	Black
Range	EasyLogic
Network frequency	50 Hz 60 Hz
Width	181 mm
Mounting mode	DIN rail mount Panel-mounted
Product certifications	RCM[RETURN]cUL listed[RETURN]UL listed
Maximum power consumption in W	8 W
Power consumption in VA	14 VA
Ambient air temperature for storage	-20...70 °C
Display type	Without display
IP degree of protection	IP20
Ambient air temperature for operation	0...50 °C at normal operation
Input/output type	8 universal I/O
Input voltage	0...10 V DC for universal input
Relative humidity	0...95 % RH, non-condensing
Memory type	6 MB internal 32 MB flash
Communication port support	RS485
[Us] rated supply voltage	24 V AC +/- 15 %
Number of outputs	3 form A relay output 1 form C relay
Height	110 mm
Depth	64 mm
Protection type	Internal fuse MOV suppression
Output voltage	0...10 V DC for analog output
Range of product	EasyLogic
Range	EasyLogic

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Complementary

Product compatibility	BACnet field controller
Product brand	Schneider Electric
Switching frequency	25 Hz
Backup time	7 days
Flame retardance	UL94-V0
Communication port protocol	BACnet MS/TP
Processor name	ARM Cortex-A7 single core 500 MHz SRAM 6 MB FRAM 8 kB Flash 32 MB
Standards	EN 61000-6-3 EN 50491-5-2 UL 2043 EN 61000-6-2 EN 50491-5-3 EN 60730-1 EN 60730-2-11 EN 50491-3 UL 916 ICES-003
Range compatibility	EasyLogic controller
Power consumption in VA	14 VA

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.2 cm
Package 1 Width	6.6 cm
Package 1 Length	18 cm
Package 1 Weight	398 g
Unit Type of Package 2	S02
Number of Units in Package 2	7
Package 2 Height	39.8 cm
Package 2 Width	29.9 cm
Package 2 Length	15 cm
Package 2 Weight	3.216 kg
Unit Type of Package 3	P06
Number of Units in Package 3	168
Package 3 Height	60 cm
Package 3 Width	80 cm
Package 3 Length	103 cm
Package 3 Weight	88 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes
Halogen content performance	Halogen free plastic parts product