

SXWRCF16A10003

Controller, SpaceLogic RP-C, 16 points, 8 universal I/O, 4 solid-state relay, 3 form A relay, 1 form C high power relay



Main

Range	EcoStruxure Building Operation
Product name	SpaceLogic room purpose controller
Device short name	RP-C-16A-F-230V
Product brand	Schneider Electric
Product or component type	Programmable controllers
Device application	HVAC Low voltage fan coil Chilled beam
[Us] rated supply voltage	207...253 V AC
Digital output	4 solid state 3 relay control circuit 1 relay voltage circuit
Discrete output voltage	0...10 V for output circuit 250 V AC for control relay 30 V DC for control relay 250 V AC for voltage relay 24 V DC for voltage relay 24 V AC for solid state output <= 30 V DC for solid state output
Discrete output current	2 mA for load 2 A for solid state output (DO1...DO4) 4 A for control relay (DO5...DO7) 12 A for voltage relay (DO8)

Complementary

Network frequency	50 Hz 60 Hz
Maximum power consumption in VA	65 VA
Discrete input voltage	0...10 V
Discrete input voltage type	DC
Product compatibility	Xenta I/NET Continuum Balco Satchwell Honeywell Johnson Control Invensys (FD) Linx Technologies antenna SmartX living space sensor
Analogue input type	Configurable voltage, current or probe 0...2 mA Configurable voltage, current or probe 0...10 V input voltage Configurable voltage, current or probe 20 kOhm connection of probes Configurable voltage, current or probe 10 kOhm connection of probes Configurable voltage, current or probe 2.2 kOhm connection of probes Configurable voltage, current or probe 1.8 kOhm connection of probes Configurable voltage, current or probe 1 kOhm connection of probes
Universal Input/outputs number	8
Temperature probe type	LG-Ni 1000 - 50...150 °C Ni 1000 - 50...150 °C Pt 1000 - 50...150 °C
Discrete input current	2.4 mA

Input impedance	100 kOhm for voltage circuit 47 Ohm for current circuit
Maximum current per output common	4 A at COM 1 + COM 2
Absolute accuracy error	+/- 7 mV plus + 0.2 % of reading for voltage +/- 0.01 mA plus + 0.4 % of reading for current +/- 0.5 °C for - 50...70 °C
Switching frequency	25 Hz
Mechanical durability	100000 Cycles for control relay 100000 cycles for voltage relay
Protection type	Internal fuse Built-in by varistor
Processor name	ARM Cortex-A7
Memory description	Internal 6 MB Flash 48 MB Internal data storage (FRAM) 128 kB
Backup time	7 days
Realtime clock	With
Clock drift	1 min/month at 25 °C
Function available	PWM
Integrated connection type	Port with USB 2.0 type B connector and mini USB interface Port with USB host port type A connector RS485 sensor with bus connector RS485 room picto with bus connector
Communication port protocol	BACnet IP Bluetooth 5.0 LE - SMA
Port Ethernet	10/100BASE-TX 2 port
Communication service	RSTP (Ring topology support) Programming
Topology	Daisy chain Star Ring
Local signalling	1 LED (green) for status
Display type	Without display
Electrical connection	Screw terminals, 12 terminal(s) for inputs and outputs Screw terminals, 10 terminal(s) output Screw terminals, 3 terminal(s) power supply Screw terminals, 3 terminal(s) form C relays SMA antenna with cable, 1 terminal(s)
Cable length	3 m for USB port
Insulation	Between output and ground at 3000 V AC Between power output and ground at 5000 V AC
Material	ABS/PC
Mounting support	DIN rail wall-mount
Height	110 mm
Depth	64 mm
Width	180 mm
Net weight	472 g

Environment


Standards	EN 60730-1 EN 60730-2-11 EN 50491-3
Product certifications	BTL[RETURN]CULus[RETURN]CE[RETURN]RCM[RETURN]Eu.BAC
Electromagnetic compatibility	Electromagnetic emission conforming to EN 61000-6-3 Electromagnetic emission conforming to EN 50491-5-2 Immunity to electromagnetic emissions conforming to EN 61000-6-2 Immunity to electromagnetic emissions conforming to EN 50491-5-3 Radiated emission conforming to EN 300-328
Ambient air temperature for operation	0...50 °C
Ambient air temperature for storage	-20...70 °C
Relative humidity	0...95 %, non-condensing
IP degree of protection	IP20

Pollution degree	2
Flame retardance	UL94-5V

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11 cm
Package 1 Width	6.4 cm
Package 1 Length	18 cm
Package 1 Weight	800 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free plastic parts product