Product data sheet Characteristics

SXWREDALI110001

Light expansion module, SpaceLogic RP Expansion Modules, DALI





Main

Range	EcoStruxure Building Operation
Product name	SmartX Room Purpose Controller
Device short name	RP-C-EXT-DALI-1
Product brand	Schneider Electric
Product or component type	Bus extension module
[Us] rated supply voltage	100277 V AC
Discrete input number	4, dry contact
Discrete output number	4 lamp
Discrete output voltage	100277 V AC for power supply output
Discrete output current	64 mA for lamp (DA+, DA-)

Complementary

Supply voltage limits	90304 V
Network frequency	50 Hz
	60 Hz
Maximum power consumption in VA	10 VA
Power supply input current	2.2 mA at 5 V
Input type	Digital
Range compatibility	EcoStruxure Building Operation software
Maximum current per output common	250 mA at DA+, DA-
Processor name	ARM Cortex-M4
Memory description	Flash 1024 kB
	Internal RAM 320 kB
Data backed up	16 MB flash memory
Function available	Light control
	DALI bus terminal
Control type	ADDRESS, range: 09 with rotary switch(es)
Communication port protocol	Ethernet Modbus TCP/IP daisy chain
	RS485
Port Ethernet	10/100BASE-T 2 port RJ45
Local signalling	LED (green/red) for status indication
Electrical connection	2-pin terminal block, 4 terminal(s) input circuit
	2-pin terminal block, 4 terminal(s) output
	3-pin terminal block, 1 terminal(s) power supply
Mounting support	DIN rail
	Surface mount
Colour	Black
Height	110 mm
Depth	64 mm
Width	198 mm

Environment

Standards	EN 60730-1
	EN 60730-2-11 EN 50491-3
	UL 916
Product certifications	RCM
Electromagnetic compatibility	Electromagnetic emission conforming to EN 61000-6-3
	Electromagnetic emission conforming to EN 50491-5-2
	Electromagnetic emission class B conforming to FCC part 15 Subpart B
	Immunity to electromagnetic emissions conforming to EN 50491-5-3
	Immunity to electromagnetic emissions conforming to EN 61000-6-2
Ambient air temperature for operation	050 °C
Ambient air temperature for storage	-2070 °C
Relative humidity	2090 %, non-condensing
IP degree of protection	IP20
Pollution degree	2
Flame retardance	UL94-V0
Overvoltage category	III

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	21.2 cm	
Package 1 Width	7.0 cm	
Package 1 Length	13.5 cm	
Package 1 Weight	483.0 g	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☐ End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

