SXWSATXXXSLW

SmartX Temperature Sensor, 3 Buttons/LCD, Setpoint, with Optimum White Cover



Main	
Product or component type	Sensor
Type of measurement	Temperature
Device application	HVAC Temperature control Fan speed controller
Display size	30 x 17 mm
Flame retardance	UL94-V0
IP degree of protection	IP20
Location	Living space
Depth	24 mm
Height	115 mm
Width	85 mm
Standards	UL 916 FCC part 15 class B
Colour	White
Ambient air temperature for operation	050 °C
Relative humidity	095 %
Sensor type	Transmitter
Surface finish	Glossy
Product name	SmartX Living Space Sensor
Function available	Override switches Setpoint adjustment
Product specific application	Cooling Heating
Range	SpaceLogic

Complementary

Complementary	
Device presentation	Complete product
Max power consumption in W	2 W
Information displayed	Temperature Operating mode Heating/cooling symbol
Range compatibility	EcoStruxure Building Operation SmartX Room Purpose Controller programmable controllers
Control type	+ button - button Present/absent symbol button
Local signalling	1 red, green and blue LED modulating , function: heating or air-conditioning application
Material	ABS (acrylonitrile butadiene-styrene)
[Us] rated supply voltage	24 V DC
Display type	LCD display
Communication port support	RJ45

Environment

Temperature setting range	050 °C	
Measurement range	050 °C temperature	
Product certifications	CE conforming to EN 61000-6-3[RETURN]RCM[RETURN]EAC[RETURN]ICES-003	

Packing Units

PCE
1
4.8 cm
9.7 cm
14.0 cm
80.0 g
_

Offer Sustainability

EU RoHS Directive	Compliant EEU RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins