

SXWSBTHXXSXX

Sensor Base for SmartX IP Controllers Temp,
Humidity - Cover not included



Main

Range	SpaceLogic
Product or component type	Sensor
Product name	SmartX Living Space Sensor
Type of measurement	Humidity Temperature
Product certifications	CE conforming to EN 61000-6-3[RETURN]RCM[RETURN]EAC[RETURN]ICES-003
Display type	Without display
Flame retardance	UL94-V0
IP degree of protection	IP20
Location	Living space
Depth	20.7 mm
Height	111.6 mm
Width	81.2 mm
Ambient air temperature for operation	0...50 °C
Standards	UL 916 FCC part 15 class B
Colour	White
Sensor type	Transmitter
[Us] rated supply voltage	24 V DC
Device presentation	Without cover

Complementary

Communication port support	RJ45
Material	ABS (acrylonitrile butadiene-styrene) GF10 FR
Function available	With temperature sensor With humidity sensor
Hysteresis	1.5 %
Max power consumption in W	2 W
Supply	Via bus connector
Output type	Sensor bus
Range compatibility	EcoStruxure Building Operation SmartX Room Purpose Controller programmable controllers EcoStruxure Building Operation SmartX Living Space Sensor sensor coverplate

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.8 cm
Package 1 Width	9.67 cm
Package 1 Length	14 cm
Package 1 Weight	121 g

Offer Sustainability

EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information