SXWSC3XSELXB

SmartX Cover Plate, for Sensor Base, 3 Buttons, No Display, Setpoint, Override, Optimum Black Cover



Main Range

Range	SpaceLogic	
Product or component type	Cover	
Product name	SmartX Living Space Sensor	
Device application	HVAC Control	
Product certifications	CE conforming to EN 61000-6-3[RETURN]RCM[RETURN]EAC[RETURN]ICE	S-(
Display type	Without display	
Flame retardance	UL94-V0	
IP degree of protection	IP20	
Location	Living space	
Depth	20 mm	
Height	115 mm	
Width	85 mm	
Ambient air temperature for operation	050 °C	
Standards	UL 916 FCC part 15 class B	tained herein.
Colour	Black	ainea police
[Us] rated supply voltage	24 V DC	of the products contained herein.
Device presentation	Cover plate	proat
Surface finish	Matt £	of the
Local signalling	1 red, green and blue LED modulating , function: heating or air-conditioning application	ertormance of the
		PTOT

Complementary

Material	ABS (acrylonitrile butadiene-styrene) GF10 FR
Function available	Override switches Setpoint adjustment
Supply	Base
Connections - terminals	Bus terminal (back)
Range compatibility	EcoStruxure Building Operation SmartX Room Purpose Controller programmable controllers EcoStruxure Building Operation SmartX Living Space Sensor base unit

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	4.8 cm	
Package 1 Width	9.7 cm	
Package 1 Length	14.0 cm	
Package 1 Weight	121.0 g	

Offer Sustainability

EU RoHS Directive	Compliant E EU RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins