

SXWSCBPSELXW

SmartX Cover Plate, for Sensor Base, Blank, PIR, Optimum White Cover



Main

Range	SpaceLogic
Product or component type	Cover
Product name	SmartX Living Space Sensor
Device application	HVAC Control
Product certifications	CE conforming to EN 61000-6-3 RCM EAC ICES-003
Display type	Without display
Flame retardance	UL94-V0
IP degree of protection	IP20
Location	Living space
Depth	20 mm
Height	115 mm
Width	85 mm
Ambient air temperature for operation	0...50 °C
Standards	UL 916 FCC part 15 class B
Colour	White
Sensor type	PIR
[Us] rated supply voltage	24 V DC
Device presentation	Cover plate
Surface finish	Matt

Complementary

Material	ABS (acrylonitrile butadiene-styrene) GF10 FR
Supply	Base
Connections - terminals	Bus terminal (back)
Movement detection area	4 m at 140° (1.35 m mounting) 5 m of radius (wall) at 110° (1.35 m mounting) 6 m at 60° (1.35 m mounting)
Range compatibility	EcoStruxure Building Operation SmartX Room Purpose Controller programmable controllers EcoStruxure Building Operation SmartX Living Space Sensor base unit

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.8 cm
Package 1 Width	9.7 cm
Package 1 Length	14.0 cm
Package 1 Weight	121.0 g

Offer Sustainability

EU RoHS Directive	Compliant  EU RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins