

SXWUI8A4H10001

Central I/O module, SpaceLogic, 8 universal inputs, 4 analog outputs, hand control/override switches



Main

Net weight	152 g
Product or component type	I/O module
Device short name	UI-8/AO-4-H
Height	114 mm
Flame retardance	UL94V0-5VB
Width	90 mm
Product certifications	ICES-003[RETURN]FCC part 15 class B[RETURN]CE[RETURN]RCM[RETURN]UL
Ambient air temperature for storage	-20...70 °C
Depth	64 mm
Ambient air temperature for operation	0...50 °C
IP degree of protection	IP20
Power consumption in W	3.2 W
Input/output type	Universal input
Relative humidity	0...95 % non-condensing
Number of outputs	4 analog output
[Us] rated supply voltage	24 V DC
Product name	I/O Modules
Product brand	Schneider Electric
Range	EcoStruxure Building Operation

Complementary

Electrical connection	Plug-in sub-base
Control type	With integrated switch for off/on/automatic
Product compatibility	Balco Johnson Control Continuum I/NET Xenta Satchwell Honeywell
Switching frequency	25 Hz
Discrete input number	8
Mounting support	DIN rail Wall
Analogue input type	Configurable voltage, current or probe 0...20 mA Configurable voltage, current or probe 0...10 V input voltage Configurable voltage, current or probe 20 kOhm connection of probes Configurable voltage, current or probe 10 kOhm connection of probes Configurable voltage, current or probe 2.2 kOhm connection of probes Configurable voltage, current or probe 1.8 kOhm connection of probes Configurable voltage, current or probe 1 kOhm connection of probes Configurable voltage, current or probe 10 kOhm with shunt
Local signalling	LED (green/red) for high signal level LED (green/red) for low signal level
Range compatibility	EcoStruxure Building Operation TB-IO-W1 terminal base

Standards	UL 864 UL 916 FCC CFR47 part 15
Material	ABS + PC

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.6 cm
Package 1 Width	11.7 cm
Package 1 Length	9.0 cm
Package 1 Weight	177.6 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes
Halogen content performance	Halogen free plastic parts & cables product