# SXWUI8V4X10001

Central I/O module, SpaceLogic, 8 universal inputs, 4 analog voltage outputs





#### Main Net w

Net weight	152 g
Product or component type	I/O module
Device short name	UI-8/AO-V-4
Height	114 mm
Flame retardance	UL94V0-5VB
Width	90 mm
Product certifications	ICES-003[RETURN]FCC part 15 class B[RETURN]CE[RETURN]RCM[RETURN]UL
Ambient air temperature for storage	-2070 °C
Depth	64 mm
Ambient air temperature for operation	050 °C
IP degree of protection	IP20
Power consumption in W	1 W
Input/output type	Universal input
Relative humidity	095 % non-condensing
Number of outputs	4 analog output
[Us] rated supply voltage	24 V DC
Product name	I/O Modules
Product brand	Schneider Electric
Range	EcoStruxure Building Operation

### Complementary

o o mpromornary	
Electrical connection	Plug-in sub-base
Control type	Without
Product compatibility	Continuum
	Johnson Control
	Balco
	I/NET
	Xenta
	Satchwell
	Honeywell
Switching frequency	25 Hz
Discrete input number	8
Mounting support	DIN rail
	Wall
Analogue input type	Configurable voltage, current or probe 020 mA
	Configurable voltage, current or probe 010 V input voltage
	Configurable voltage, current or probe 20 kOhm connection of probes
	Configurable voltage, current or probe 10 kOhm connection of probes
	Configurable voltage, current or probe 2.2 kOhm connection of probes
	Configurable voltage, current or probe 1.8 kOhm connection of probes
	Configurable voltage, current or probe 1 kOhm connection of probes
	Configurable voltage, current or probe 10 kOhm with shunt
Local signalling	LED (green/red) for high signal level
	LED (green/red) for low signal level
Range compatibility	EcoStruxure Building Operation TB-IO-W1 terminal base

Standards	UL 864 UL 916 FCC CFR47 part 15	
Material	ABS + PC	

## Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	5.7 cm	
Package 1 Width	11.7 cm	
Package 1 Length	9.2 cm	
Package 1 Weight	169.6 g	

#### Offer Sustainability

onor ouclamasing	
Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	<sup>™</sup> Yes
Environmental Disclosure	<sup>☑</sup> Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes
Halogen content performance	Halogen free plastic parts & cables product