



Main

| | |
|---|---|
| Range of product | TransferPacT |
| Product or component type | Automatic transfer switch |
| Device application | Change source of supply |
| Poles description | 4P |
| Network type | AC |
| Network frequency | 50/60 Hz |
| Downside connection | Screwed |
| Mounting mode | Fixed |
| Upside connection | Screwed |
| Contact position indicator | Yes |
| [Icm] rated short-circuit making capacity | 15 KA switch-disconnector alone 400 V AC at 50 Hz 75 kA with upstream protection circuit breaker 400 V AC at 50 Hz |
| Suitability for isolation | Yes |

Complementary

| | |
|---|------------------------------------|
| Transfer switch class | PC |
| Number of contact position | 3 |
| Signal contacts composition | 1 NO + 2 NC 1 NC + 2 NO 2 NO |
| Utilization category | AC-32B |
| [Ue] rated operational voltage | 400 V AC 50/60 Hz |
| Control type | Rotary knob Selector switch |
| Operating mode | Automatic Manual |
| Mounting support | Plate DIN rail |
| Locking options description | Padlock in OFF position |
| Rated duty | Uninterrupted |
| [Ui] rated insulation voltage | Switch: 800 V Controller: 500 V |
| [Uimp] rated impulse withstand voltage | Switch: 6 kV Controller: 6 kV |
| [Ie] rated operational current | 100 A |
| Mechanical interlocking | With mechanical interlocking |
| Mechanical durability | 8000 cycles |
| Connection pitch | 18 mm |
| [Icw] rated short-time withstand current | 5 kA during 0.1 s |
| Height | 145 mm |
| Width | 306 mm |
| Depth | 94 mm |
| Net weight | 3.4 kg |
| [Ith] conventional free air thermal current | 100 A at 60 °C |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

| | |
|---------------------------------------|--|
| Standards | IEC 60947-6-1 |
| Product certifications | CE[RETURN]CB[RETURN]CCC |
| IP degree of protection | Front face: IP40 auto mode Inside the enclosure: IP20 manual mode |
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -35...85 °C |
| Pollution degree | 3 |

Packing Units

| | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 14.800 cm |
| Package 1 Width | 21.200 cm |
| Package 1 Length | 36.500 cm |
| Package 1 Weight | 4.125 kg |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant with Exemptions |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |