



Main

| | |
|---|--|
| Range of product | TransferPacT |
| Product or component type | Automatic transfer switch |
| Device application | Change source of supply |
| Poles description | 4P |
| Network type | AC |
| Network frequency | 50/60 Hz |
| Downside connection | Screwed |
| Mounting mode | Fixed |
| Upside connection | Screwed |
| Contact position indicator | Yes |
| [Icm] rated short-circuit making capacity | 30 kA switch-disconnector alone 400 V AC at 50 Hz 330 kA with upstream protection circuit breaker 400 V AC at 50 Hz |
| Suitability for isolation | Yes |

Complementary

| | |
|--|---|
| Transfer switch class | PC |
| Number of contact position | 3 |
| Signal contacts composition | 1 NO + 2 NC 1 NC + 2 NO 2 NO |
| Utilization category | AC-33B |
| [Ue] rated operational voltage | 400 V AC 50/60 Hz |
| Control type | 4 push-buttons |
| Operating mode | Automatic Manual |
| Display type | LCD screen |
| Mounting support | Plate |
| Locking options description | Padlock in OFF position Padlock in SI / SII position |
| Rated duty | Uninterrupted |
| [Ui] rated insulation voltage | Switch: 800 V Controller: 500 V |
| [Uimp] rated impulse withstand voltage | Switch: 8 kV Controller: 6 kV |
| [Ie] rated operational current | 200 A |
| Mechanical interlocking | With mechanical interlocking |
| Mechanical durability | 10000 cycles |
| Connection pitch | 35 mm |
| Local signalling | LED indicator (green) for power ON LED indicator (red) for alarm |
| [Icw] rated short-time withstand current | 10 kA during 0.5 s 15 kA during 0.1 s |
| Height | 341 mm |
| Width | 370 mm |
| Depth | 185.8 mm |

| | |
|---|----------------|
| Net weight | 13.3 kg |
| [lth] conventional free air thermal current | 200 A at 60 °C |

Environment

| | |
|---------------------------------------|--|
| Standards | IEC 60947-6-1 |
| Product certifications | CE[RETURN]CB[RETURN]CCC |
| IP degree of protection | Front face: IP40 auto mode Inside the enclosure: IP20 manual mode |
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -40...85 °C |
| Pollution degree | 3 |

Packing Units

| | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 43.600 cm |
| Package 1 Width | 41.000 cm |
| Package 1 Length | 45.000 cm |
| Package 1 Weight | 13.000 kg |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation |  REACH Declaration |
| EU RoHS Directive | Compliant with Exemptions |
| Mercury free | Yes |
| China RoHS Regulation |  China RoHS Declaration |
| RoHS exemption information |  Yes |
| Environmental Disclosure |  Product Environmental Profile |
| Circularity Profile |  End Of Life Information |