TCSESPU093F2CS0

switch, Modicon Networking, premium unmanaged switch, 7 ports for copper, 2 ports for fiber optic single-mode



Main Range of product ConneXium Product or component Ethernet TCP/IP unmanaged switch type Concept Transparent Ready Communication port Ethernet TCP/IP protocol Port Ethernet 10/100BASE-TX - 7 port(s) copper cable 100BASE-FX - 2 port(s) fiber optic Maximum number of Unlimited switches in cascade

Complementary

Complementary		
Integrated connection type	Shielded RJ45 copper cable Duplex SC fiber optic	
Transmission support medium	Twisted shielded pairs cable CAT 5E for copper cable Single mode optical fiber for fiber optic	
Maximum cable distance between devices	100 m copper cable	
Optic fiber length	32.5 km 9/125 μm	
Attenuation	016 dB (9/125 μm)	
Ethernet service	Multicast filtering Data stream control	
Communication service	Quality of Service (QoS)	
[Us] rated supply voltage	1224 V	
Supply voltage limits	9.632 V DC SELV	
Power consumption in W	6.9 W	
Electrical connection	Removable connector 6 ways power supply	
Mounting support	35 mm symmetrical DIN rail	
Marking	CE UL RCM	
Local signalling	1 dual colour LED (green/yellow) for P1 P2 power supplies 1 LED per channel (yellow) for data rate (ETH LINK) 1 dual colour LED (green/yellow) for link status	
Ethernet cabling system	TF switches	
Width	56 mm	
Height	135 mm	
Depth	117 mm	
Net weight	0.510 kg	

Environment

Ambient air temperature for operation	-4070 °C	
Relative humidity	1095 % non-condensing	
IP degree of protection	IP40	
Directives	2014/35/EU - low voltage directive 2014/30/EU - electromagnetic compatibility	
Standards	UL 61010 EN/IEC 61131	
Product certifications	CE[RETURN]UL[RETURN]RCM	

Packing Units

0	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13.5 cm
Package 1 Width	16.2 cm
Package 1 Length	23.5 cm
Package 1 Weight	801.0 g
Unit Type of Package 2	S04
Number of Units in Package 2	8
Package 2 Height	30.0 cm
Package 2 Width	40.0 cm
Package 2 Length	60.0 cm
Package 2 Weight	6.56 kg

Offer Sustainability

EU D 110 D: ()	N. C. II. C. CELID HOL. I
EU RoHS Directive	Not applicable, out of EU RoHS legal scope

Contractual warranty

147	40
Warranty	18 months
	To mondie

TCSESPU093F2CS0

Dimensions

