



Main

Range of product	Modicon M171/M172
Product or component type	Display module
Supply	External source

Complementary

Display type	LCD display Colour touchscreen
Display resolution	320 x 240 pixels
Colour	Grey
[Us] rated supply voltage	24 V AC/DC
Power consumption in W	1.3 W 3.2 VA
Overvoltage category	II
Product compatibility	Logic controller M171 Logic controller M172
Height	96 mm
Width	134 mm
Depth	35 mm
Net weight	0.175 kg

Environment

Directives	2014/30/EU - electromagnetic compatibility
Standards	UL 60730-1 UL 60730-2-9 CSA E60730-2-9 IEC 61000-4-3 IEC 61000-4-6 CAN/CSA-E60730-1 IEC 61000-4-2 IEC 61000-4-4 IEC 60730-1 IEC 61000-4-11 IEC 61000-4-5 IEC 60730-2-9 UL 94
Product certifications	RCM[RETURN]CE[RETURN]cURus[RETURN]EAC[RETURN]CSA
Ambient air temperature for operation	-20...60 °C
Ambient air temperature for storage	-30...60 °C
IP degree of protection	IP65 front panel:
Pollution degree	2

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13.2 cm
Package 1 Width	18.8 cm
Package 1 Length	9.4 cm
Package 1 Weight	288.0 g
Unit Type of Package 2	S02
Number of Units in Package 2	6
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	2.049 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Upgradeability	Upgradeable through digital modules and upgraded components