



Main

Product or component type	Modbus RS485 communication module
Device application	Communication
Bus type	Modbus

Complementary

Function available	Modbus communication module
Physical interface	RS485
[Ui] rated insulation voltage	30 V DC
Communication network type	Modbus, Modbus RTU even parity, at 4800 bauds Modbus, Modbus RTU even parity, at 9600 bauds Modbus, Modbus RTU even parity, at 19200 bauds
Addressing	0...248
Type of cable	Shielded twisted pair 1.5 mm ²
Tightening torque	0.6 N.m +/- 0.1 N.m
Mounting mode	Plug-in
Mounting position	In square
Localisation on device	Front face
Connections - terminals	Screw-clamp terminals
Height	56.5 mm
Depth	69 mm
Width	20 mm
Net weight	40 g
Accessory / separate part category	Communication accessories

Environment

IP degree of protection	IP20
Pollution degree	3

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.650 cm
Package 1 Width	6.900 cm
Package 1 Length	2.000 cm
Package 1 Weight	92.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	20
Package 2 Height	15.000 cm

Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	2.100 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information