

# Product data sheet

## Characteristics

### TPCDIO13

function module, TransferPacT, fire protection, 230V AC constant, input signal



#### Main

Range of product	TransferPacT
Product or component type	I/O module
Device application	Signalling

#### Complementary

Auxiliary contact composition	1 NO
Signalling function	Fire protection (transfer to off position)
Auxiliary connection terminal	Screw clamp terminal 0.05...2.6 mm <sup>2</sup>
Mounting mode	Plug-in
Mounting position	Left-bottom
Maximum input current	10 mA 230 V AC +/- 20 %
[Ui] rated insulation voltage	300 V AC
Tightening torque	0.6 N.m +/- 0.1 N.m
Height	56.5 mm
Width	20 mm
Depth	69 mm
Net weight	40 g
Accessory / separate part category	Signalling accessory

#### Environment

IP degree of protection	IP20
Pollution degree	3

#### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.400 cm
Package 1 Width	10.500 cm
Package 1 Length	10.700 cm
Package 1 Weight	86.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	20
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	1.996 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
RoHS exemption information	 Yes
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
Circularity Profile	 <a href="#">End Of Life Information</a>