

# Product data sheet

## Characteristics

### TPCDIO14

function module, TransferPacT, fire protection, dry contact, passive, input signal



#### Main

Range of product	TransferPacT
Product or component type	I/O module Dry contact
Device application	Signalling

#### Complementary

Auxiliary contact composition	1 NO
Signalling function	Fire protection (transfer to off position)
Auxiliary connection terminal	Screw clamp terminal 0.05...2.6 mm <sup>2</sup>
Mounting mode	Plug-in
Mounting position	Left-bottom
Minimum input current	5 mA
[Ui] rated insulation voltage	30 V DC
Tightening torque	0.6 N.m +/- 0.1 N.m
Height	56.5 mm
Width	20 mm
Depth	69 mm
Accessory / separate part category	Signalling accessory

#### Environment

IP degree of protection	IP20
Pollution degree	3

#### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.65 cm
Package 1 Width	6.9 cm
Package 1 Length	2 cm
Package 1 Weight	140 g

#### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes

---

China RoHS Regulation	<input checked="" type="checkbox"/> China RoHS Declaration
RoHS exemption information	<input checked="" type="checkbox"/> Yes
Environmental Disclosure	<input checked="" type="checkbox"/> Product Environmental Profile
Circularity Profile	<input checked="" type="checkbox"/> End Of Life Information

---